

## 腔体耦合器 ( TAPPER )

型号 Model	CP-2.5G5-01A	CP-2.5G6-01A	CP-2.5G7-01A
频率范围 Frequency range	800-2500 MHz	800-2500 MHz	800-2500 MHz
耦合度 Coupling	5dB±0.6	6dB±0.6	7dB±0.8
插入损耗 Insertion loss	≤2.1dB	≤1.7dB	≤1.3dB
驻波 VSWR	≤1.4	≤1.4	≤1.4
阻抗 Impedance	50Ω	50Ω	50Ω
功率 power	200W	200W	200W
接头 Connector	N-F	N-F	N-F
工作温度 Operating Temperature	-30 □+70	-30 □+70	-30 □+70

型号 Model	CP-2.5G10-01A	CP-2.5G15-01A	CP-2.5G20-01A
频率范围 Frequency range	800-2500 MHz	800-2500 MHz	800-2500 MHz
耦合度 Coupling	10dB±1.0	15dB±1.0	20dB±1.0
插入损耗 Insertion loss	≤0.8dB	≤0.35dB	≤0.3dB
驻波 VSWR	≤1.4	≤1.4	≤1.4
阻抗 Impedance	50Ω	50Ω	50Ω
功率 power	200W	200W	200W
接头 Connector	N-F	N-F	N-F
工作温度 Operating Temperature	30 □+70	-30 □+70	-30 □+70

